

CORDRAIN 20-250

Cordrain drainage consists of a corrugated HDPE core (16 or 20 mm high) with a geotextile filter membrane on one side and is available in different strenghts (crush resistance) to suit your specific application. Cordrain is used for horizontal drainage

in many different applications in roofgardens, podiumdecks, road- and lightrail hardscaped construction. with a width of 1.1 m and a lenght of 25 m. per role, large areas can quickly be covered.

Applications

- Green Roofs
- Drainage

GENERAL		SIZE		
Brand	Drain Products Europe	Size	EN 964-1 EN ISO 9863-1	25.000 x 1.100 x 20 mm (l x w x h), 27,5 m²
Product name	Cordrain 20-250			
Item nr.	4000005			
Color	Yellow core in white geotextile			
Material	HDPE core with Polypropene, non woven, thermally bonded geotextile wrap	Mass per unit area	EN ISO 9864	1200 g/m²
Material description	Drainage	Dynamic perforation resistance	EN ISO 13433	33 mm
Recycled/Virgin	Virgin	Water flow capacity in the plane	EN ISO 12958	3,12 l/ms (i=1, 20 kPa)
Certification	CE 0334 CPR 0003	Tensile strength MD	EN ISO 10319	17 kN/m
		Tensile strength CMD	EN ISO 10319	17 kN/m
		Tensile strain at Max Strength MD	EN ISO 10319	61,80%
		Tensile strain at Max Strength CMD	EN ISO 10319	59,90%

CORDRAIN 20-250

GEOTEXTILE

Thickness under 2 kPa	EN ISO 9863-1	0,45 mm
Weight	EN ISO 9864	125 g/m ²
Melting point		n.a
Tensile strength MD	EN ISO 10319	21,7 kN/m
Tensile strength CMD	EN ISO 10319	n.a
Tensile strain at Max Strength MD	EN ISO 10319	n.a
Tensile strain at Max Strength CMD	EN ISO 10319	n.a
Opening size	EN ISO 12956	130 micron
Water Permeability	EN ISO 11058	0,05 m/s
Durability	EN ISO 13252	> 100 years in natural soils
Necessary ancillaries (included)		n.a

GEOSPACER

Thickness under 2 kPa	EN ISO 9863-1	20 mm
Crush Resistance	EN ISO 25619-2	275 kPa
Compressive creep thickness	EN ISO 25619-1	-5% (100 kPa/10yrs)

PACKAGING

Packaging	Role, 1.500 x 1.100mm (diam. x w) approx.
Storage instruction	Exposure to UV without protection should not exceed two weeks. To be covered within 2 weeks after installation.

Notes

Permavoid Ltd. will not be held liable if our products are used in a manner inconsistent with our requirements, standards or the purposes indicated in the standards. Standards can be obtained at www.permavoid.com. This document is not contractual. With our constant concern for improvements, the information this document contains and the products presented may be modified without notice. The latest version of this document can be obtained at www.permavoid.com. Please get in touch with us if you require any further documentation or information.

Data Sheet: PDS-20
Last revised: January 2021

Permavoid Head Office

Kattenburgerstraat 5
1018 JA | Amsterdam | The Netherlands
www.permavoid.com | info@permavoid.co.uk

Permavoid Ltd. is part of the Polypipe Group.