

DRAINTILE 50

In urban or paved situations where drainage is needed within tight height limitations, the high

strength DrainTile 50 are used. They form a continuous drainage surface area with high capacity.

Applications

- Green Roofs
- Drainage

GENERAL

| | |
|-----------------------------|---------------|
| Brand | Permavoid |
| Product name | DrainTile 50 |
| Item nr. | 5000002 |
| Color | Black |
| Material | Polypropylene |
| Material description | Drainage |
| Recycled/Virgin | Recycled |
| Certification | |

SIZE

| | | |
|-----------------------------|------------------------|---|
| Size | EN 964-1 EN ISO 9863-1 | 500 x 500 x 50mm +/- 1.4% (L x w x h) |
| Mass per unit area | EN ISO 9864 | 4.2 kg/m ² |
| Void ratio | | 96% |
| Compression strength | ASTM D1621 | 125 T/m ² |
| Flow rate per unit | ASTM D1621 | 180 l/m |

DRAINTILE 50

PACKAGING

| | |
|------------------------|-----------------------------|
| Pallet size | 110 x 110 x 230 cm |
| Pallet weight | 190 kilo |
| Pallet capacity | 42m ² per pallet |

Notes

Permavoid Ltd. will not be held liable if our products are used in a manner inconsistent with our requirements, standards or the purposes indicated in the standards. Standards can be obtained at www.permavoid.com. This document is not contractual. With our constant concern for improvements, the information this document contains and the products presented may be modified without notice. The latest version of this document can be obtained at www.permavoid.com. Please get in touch with us if you require any further documentation or information.

Data Sheet: PDS-22
Last revised: January 2021

Permavoid Head Office

Kattenburgerstraat 5

1018 JA | Amsterdam | The Netherlands
www.permavoid.com | info@permavoid.co.uk

Permavoid Ltd. is part of the Polypipe Group.