

DRAINTILE 50

In urban or paved situations where drainage is needed within tight height limitations, the high

strength DrainTile 50 are used. They form a continuous drainage surface area with high capacity.

Applications

- Green Roofs
- Drainage

GENERAL

Brand	Permavoid
Product name	DrainTile 50
Item nr.	5000002
Color	Black
Material	Polypropylene
Material description	Drainage
Recycled/Virgin	Recycled
Certification	

SIZE

Size	EN 964-1 EN ISO 9863-1	500 x 500 x 50mm +/- 1.4% (L x w x h)
Mass per unit area	EN ISO 9864	4.2 kg/m ²
Void ratio		96%
Compression strength	ASTM D1621	125 T/m ²
Flow rate per unit	ASTM D1621	180 l/m

DRAINTILE 50

PACKAGING

Pallet size	110 x 110 x 230 cm
Pallet weight	190 kilo
Pallet capacity	42m ² per pallet

Notes

Permavoid Ltd. will not be held liable if our products are used in a manner inconsistent with our requirements, standards or the purposes indicated in the standards. Standards can be obtained at www.permavoid.com. This document is not contractual. With our constant concern for improvements, the information this document contains and the products presented may be modified without notice. The latest version of this document can be obtained at www.permavoid.com. Please get in touch with us if you require any further documentation or information.

Data Sheet: PDS-22
Last revised: January 2021

Permavoid Head Office

Kattenburgerstraat 5

1018 JA | Amsterdam | The Netherlands
www.permavoid.com | info@permavoid.co.uk

Permavoid Ltd. is part of the Polypipe Group.